

Features

Feed fibers for measurement with OTDR. The individually configured supply fibers are installed in a robust plastic case. Up to 4 fiber spools per case are possible. The connection tails are either factory-assembled or designed as a splice version. In order to ensure reproducible excitation conditions (encircled flux), a mode conditioner can be integrated.

Other combinations are available on requests.



Type: „factory assembled version“

Factory assembled connectors of your choice.
 Fan out leg length: 2 m
 Connector type : by choice
 Mode Conditioner: possible(only M/M type)
 Maintenance : re-termination in factory.

Type: „Splice version“

Splice your own, flexible cable pigtails with the connectors of your choice!
 2 m of fiber are housed inside the splice cassettes.
 Cable pigtails can be ordered separately.
 Pre-spliced cable pigtails available on request
 Connector type : different connectors
 (simplex or duplex)
 Fiber length : max. 1000/2000 meter
 Per fiber/ in total

Size of Case : 270 x 220 x 80 mm



While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
S. Schmidt	18.12.2013	C. Hahn	18.12.2013	003		Y. Zhang	03.04.3018