



Properties

Rosenberger Quad Connector (RQC), straight plug, with undetachable protection cap for outdoor application.

Interface

RDC, acc. to IEC 61754- 31

Material for connectors

Ferrule :	Zirconia ceramic, Ø1.25 mm
Body :	Brass, flash white bronze plating
Gasket	Silicon Rubber
Crimp Sleeve	Copper, nickel plating
Boot :	TPV

Optical data

Insertion Loss :	S/M	Typical	max.
	M/M	0.25 dB	0.50 dB
Return Loss :	S/M	0.25 dB	0.50 dB
	M/M	≥50 dB(UPC), ≥65 dB(APC)	
		≥20 dB	

Mechanical data

Mating cycle	≥ 500
Strain relief	700 N(dependent on the cable type)
Coupling torque	1.0 to 2.0 Nm

Environmental data

Operation temperature range	-40°C to +125°C
Storage temperature range	-40°C to +85°C

Limitations are possible due to the used cable type

Vibration	IEC 61300-2-1
Salt mist	IEC 61300-2-26. 30 days
Ingress Protection, mated	EN 60529 IP 67
RoHS	Compliant

Tooling

On request

Dust Cap

Metal or Plastic

Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger OSI GmbH & Co. OHG

Suitable cables

Fiber

S/M, G652D, G657A1, G657A2
 M/M, 62.5/125µm, 50/125µm OM2, OM3 and OM4
 Ø 4 – 7.5mm(Breakout or MiniBreakout)

Round Cable Types :

Packaging

Standard Packaging.

Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger OSI GmbH & Co. OHG

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
Y.Zhang	15.05.2017	H.Jungbäck	15.05.2017	002	---	Y.Zhang	15.05.2017