



MTP® (MPO) connector n x 12 fibers



Properties and applications

- MTP® (MPO) multi-fiber connector up to 72 fibers, based on n x 12 fiber MT ferrules, with strain relief and boot for round cable
- Centric coding-key
- Multimode MTP® (MPO) are acc. to world standard PC 0° polished, Singlemode APC 8°
- Polarity and gender can be changed acc. to USCONEC AEN-1405
- ¹⁾ With MTP® PRO protection cap, debris-repellent (better than anti-static), non-outgassing, halogen-free

Standards

IEC 61754-7 and EIA/TIA 604-5

Material

- Ferrule: PPS filled with glass particles
- Body: PBT, flammability UL94-V0
- Boot: TPO, flammability UL94-V0
- Protection cap: TPO, flammability UL94-V0

Optical properties

The quality feature of the connector at your product is identified by the part number:

- BASIC: Part numbers like XXXAXXXX
- PURE: Part numbers with "P" at their end, XXXAXXXXP
- LOTUS: Part numbers with "L" at their end, XXXAXXXXL

Details about PURE see Produktinfo_Qualitätsmerkmal-PURE_od, about LOTUS tbd

Applied USCONEC ferrule qualities:

	Quality features	BASIC	PURE	LOTUS
- Singlemode SM, 9/125µm all numbers of fibers		Standard	Elite	Standard
- Multimode OM2, OM3, OM4, OM5, 50/125µm up to 12 fibers		Elite	Elite	Elite
- Multimode OM2, OM3, OM4, OM5, 50/125µm larger 12 fibers		Standard	Elite	Standard

Insertion Loss IL acc. to IEC61300-3-4, Method B, against reference, maximum [dB]:

	Quality features	BASIC	PURE	LOTUS
- Singlemode SM, 9/125µm, Standard ferrule		0.60	---	tbd
- Singlemode SM, 9/125µm, Elite ferrule		0.35	0.25	tbd
- Multimode OM2, OM3, OM4, OM5, 50/125µm, Standard ferrule		0.60	---	tbd
- Multimode OM2, OM3, OM4, OM5, 50/125µm, Elite ferrule		0.35	0.25	tbd

Insertion Loss IL „random mated“ in application

Multimode OM2, OM3, OM4, OM5, 50/125µm, Elite ferrule [dB]:

- 12 fibers and OCTO 4+4: 89% lower 0.25
- 24 fibers: 80% lower 0.25

GHMT PVP certificates
 No.: c6955X-XX
 No.: c6956X-XX



Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger OSI GmbH & Co. OHG

MTP® (MPO) connector n x 12 fibers

Optical properties

Insertion Loss IL quality feature PURE "random mated" application limit value, average value [dB]:

- Singlemode SM, 9/125µm 0.15
- Multimode OM2, OM3, OM4, OM5, 50/125µm 0.15

Return Loss RL acc. to IEC61300-3-6, Method 1, against reference, minimum [dB]:

	Quality feature	BASIC	PURE	LOTUS
- Singlemode SM, 9/125µm, APC 8°		55	70	tbd
- Multimode all OM classes, PC 0°		30	30	tbd

Mechanical properties

- Mating cycles quality feature BASIC and PURE min. 500, IL increase < 0.2 dB
- Mating cycles quality feature LOTUS tbd
- Strain relief max. 100 N, dependent on cable type

Thermal properties

- Operation temperature range -40°C to +85°C, dependent on cable type
- Storage temperature range -40°C to +85°C

Cable diameters

Round cable types Ø 2.0 to 4.5 mm

Colors

Connector body / boot:

- Singlemode SM, 9/125µm, APC 8° green / black
- Multimode OM2, OM3, OM4, OM5, 50/125µm black / black

Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger OSI GmbH & Co. OHG

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
Y. Zhang	2017-03-31	H. Jungbäck	2017-03-31	004	---	H. Jungbäck	2021-09-02