



LC-COMPACT Push-Pull-Tab Connector PR



Delivery status of polarity window POL:  
 - at this connector side (B) = white  
 - at the opposite connector side (A) = black

Properties and applications

- LC-Duplex Push-Pull connector with compact and rugged housing with central strain relief and push-pull-tab, with which the connector can be plugged and un-plugged. 2-in-1 length push-pull-tab, long and short length selectable.
- A/B polarity easy and secure, toolless mechanical reversible
- For HIGH-DENSITY (HD) and ULTRA-HIGH-DENSITY (UHD) applications required
- Translucence duplex protection cap, fast and secure to handle and permeable for the light of laser pointers (visual fault locators)

Standards

LC-Duplex acc. to IEC/DINEN 61754-20 and EIA/TIA 604-10

Material

- Ferrule: Zirconia ceramic, Ø 1.25 mm
- Body: PA, PBT and PTFE, flammability UL94-V0
- Push-Pull-Tab: PBT, flammability UL94-V0
- Protection cap: TPE, flammability UL94-HB

Optical properties

The quality feature of the connector at your product is identified by the part number:

- BASIC: Part numbers like XXXAXXXX

Insertion Loss IL acc. to IEC61300-3-4, Method B, against reference, maximum [dB]:

	Quality feature	BASIC
- Singlemode SM, 9/125µm		0.30
- Multimode OM1, 62.5/125µm		0.30
- Multimode low IL OM2, OM3, OM4, OM5, 50/125µm		0.15

Connector Code

LC Compact Push Pull Tab Pol-Rev (LCC-PPT-PR) SM PC Blue, single boot blue	L70
LC Compact Push Pull Tab Pol-Rev (LCC-PPT-PR) SM UPC Blue, single boot	L71
LC Compact Push Pull Tab Pol-Rev (LCC-PPT-PR) SM 8° APC green, single boot green	L72
LC Compact Push Pull Tab Pol-Rev (LCC-PPT-PR) MM PC black, single boot black	L73

LC-COMPACT Push-Pull-Tab Connector PR

Optical properties

Return Loss RL acc. to IEC61300-3-6, Method 1, against reference, minimum [dB]:

	Quality feature	BASIC
- Singlemode SM, 9/125µm, PC 0°		45
- Singlemode SM, 9/125µm, UPC 0°		55
- Singlemode SM, 9/125µm, APC 8°		65
- Multimode all classes		35

Mechanical properties

- Mating cycles	min. 500, IL increase < 0.2 dB
- Strain relief	max. 100 N, dependent on cable type

Thermal properties

- Operation temperature range	-40°C to +85°C, dependent on cable type
- Storage temperature range	-40°C to +85°C

Cable diameters

Round cable types	Ø 2.0 to 3.0 mm
-------------------	-----------------

Colors

Connector body / boot:

- Singlemode SM, 9/125µm, PC and UPC 0°	black and blue / black
- Singlemode SM, 9/125µm, APC 8°	black and green / black
- Multimode OM3, 50/125µm	black and aqua / black
- Multimode OM4, 50/125µm	black and violet / black

2-in-1 length push-pull-tab



Polarity change

See the video of our LC-COMPACT Push-Pull-Boot. Its polarity change is equal, since it is the same connector body, the only difference is Push-Pull-Tab instead of Push-Pull-Boot.



While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Gezeichnet	Datum	Freigegeben	Datum	Rev.	Änderungsnummer	Name	Datum
H. Jungbäck	2022-01-20	R. Mees	2022-01-20	004	---	H. Jungbäck	2023-06-09